



# Service Guaranteed™ linear fluorescent lamps

are manufactured with premium materials, special phosphor blends, and feature a variety of Kelvin temperatures. Together, these components produce lamps with superior quality and high color rendering.

#### **Key Features and Benefits**

- · Rare earth trichromatic phosphors
- · High CRI (Color Rendering Index) portrays colors accurately.
- Enhances product appearance in retail applications.
- 95% lumen maintenance
- Variety of color temperatures: 4100K, 5000K and 6500K

#### **Application Information**

For use in a variety of applications, including the following:

Commercial Offices Industrial Retail Schools Hospitals Hospitality

## **Cool White High Output**

| T12    | Recessed D.C. |
|--------|---------------|
|        | Average       |
| Lumana | Rated Hours   |

| Watts | Base          | MOL | Order<br>No. | Domestic Code      | Master<br>Carton | Kelvin | CRI | Lumens | Average<br>Rated Hours<br>(3hrs./Start) |
|-------|---------------|-----|--------------|--------------------|------------------|--------|-----|--------|---|
| 110   | Recessed D.C. | 96" | 60839        | F96T12/CW/HO-O/ENV | 15               | 4100   | 62  | 8800   | 12000                                   |

#### Daylight Plus™ Series

Base

Medium BiPin

Single Pin



|        | T12 Med | lium BiPi | T12 Single Pin |   |  |  |
|--------|---------|-----------|----------------|---|--|--|
| r<br>n | Kelvin  | CRI       | Lumens         | Average<br>Rated Hours<br>(3hrs./Start) |  |  |
|        | 6500    | 89        | 2325           | 20000                                   |  |  |

4500

8

84

## **Super Series**

Watts

40

75

T8 Medium BiPin

12000

| Watts | Base         | MOL | Order<br>No. | Domestic Code      | Master<br>Carton | Kelvin | CRI | Lumens | Average<br>Rated Hours<br>(3hrs./Start) |
|-------|--------------|-----|--------------|--------------------|------------------|--------|-----|--------|---|
| 32    | Medium BiPin | 48" | 60792        | F32T8/SUPER741/ENV | 25               | 4100   | 78  | 2850   | 24000                                   |
|       | Medium BiPin | 48" | 60794        | F32T8/SUPER750/ENV | 25               | 5000   | 78  | 2850   | 24000                                   |

#### Triten® Series

T8 Medium BiPin

T8 Single Pin

| Watts | Base         | MOL | Order<br>No. | Domestic Code            | Master<br>Carton | Kelvin | CRI | Lumens | Average<br>Rated Hours<br>(3hrs./Start) |
|-------|--------------|-----|--------------|--------------------------|------------------|--------|-----|--------|---|
| 32    | Medium BiPin | 48" | 60766        | F32T8/TRITEN50/ULTRA/ENV | 25               | 5000   | 86  | 3100   | 30000                                   |
|       | Medium BiPin | 48" | 60798        | F32T8/TRITEN41/ENV       | 25               | 4100   | 86  | 2950   | 30000                                   |
|       | Medium BiPin | 48" | 60800        | F32T8/TRITEN50/ENV       | 25               | 5000   | 86  | 2850   | 30000                                   |

**Contains mercury**. **(Hg)** For more on clean up and safe disposal, visit epa.gov/cfl.

Order No.

60825

60833

MOL

48"

96"

**Domestic Code** 

F40T12/DAYLIGHTPLUS™/ENV

F96T12/DAYLIGHTPLUS™/ENV



**Central Industries, Inc.** Specializing in Long-Life, Energy-Saving Lighting Products Business Center at Owings Mills, 11438-W Cronridge Drive, Owings Mills, MD 21117 Contact us at 800-304-8484 or CustomerService@centralindustriesUSA.com www.centralindustriesUSA.com

Maste

Carto

30

15

6500



©2012 WESTINGHOUSE LIGHTING CORPORATION / WLC / 1212 / 104102