




**CENTRAL
INDUSTRIES**

COOL WHITE FLUORESCENT LAMPS

BENEFITS OF COOL WHITE FLUORESCENT LAMPS

- Available in an array of sizes and light output for general lighting applications
- Full range of energy efficient (Econo-G®) models available



Cathode Guard

Improves lumen maintenance by reducing end blackening. Lamps burn brighter, longer.

Recommended Applications: Offices, Warehouses, Factories, Parking Garages, Stairwells, Corridors



Call 800-304-8484 or FAX 800-932-1222

Central Industries, Inc.

Specializing in Long-Life, Energy-Saving Lighting Products

Business Center at Owings Mills

11433-F Cronridge Drive

Owings Mills, MD 21117

www.centralindustriesUSA.com

CustomerService@centralindustriesUSA.com



**CENTRAL
INDUSTRIES**

Cool White Fluorescent Lamps

Watts	MOL	Order No.	Code Abbreviation	Master Pack	Kelvin	CRI	Lumens	Base
20	24"	60801	F20T12/CW/ENV	30	4100	62	1200	Medium BiPin
30	36"	60802	F30T12/CW/ENV	30	4100	62	2250	Medium BiPin
34	22 ⁷ / ₁₆ "	60818	FB34T12/6/CW/ECONO-G [®] /ENV	12	4100	62	2400	Medium BiPin
34	48"	60785	F34T12/CW/ECONO-G [®] /ENV	30	4100	62	2650	Medium BiPin
39	48"	60828	F48T12/CW/ENV	30	4100	62	2900	Single Pin
50	60"	60815	F60T12/CW	15	4100	62	3450	Single Pin
57	72"	60765	F72T12/CW/ENV	15	4100	62	4450	Single Pin
60	96"	60803	F96T12/CW/ECONO-G [®] /ENV	15	4100	62	5400	Single Pin
63	48"	60829	F48T12/CW/HO/ENV	15	4100	62	4050	Recessed D.C.
75	60"	60816	F60T12/CW/HO	15	4100	62	5400	Recessed D.C.
87	72"	60831	F72T12/CW/HO/ENV	15	4100	62	6350	Recessed D.C.
95	96"	60832	F96T12/CW/HO/ECONO-G [®] /ENV	15	4100	62	8000	Recessed D.C.
110	96"	60839	F96T12/CW/HO-O/ENV	15	4100	62	8800	Recessed D.C.
215	96"	60813	F96T12/CW/VHO	15	4100	62	16000	Recessed D.C.

General Information

Ballast Recommendations

For optimal performance, lamps should be used with high power factor ballasts that meet ANSI standards specified for the lamp's wattage and operating characteristics (i.e. wattage, HO, VHO). Most lamps are designed to operate on rapid start ballasts. T8 lamps operate on T8 ballasts only, F40T12 and F40T10 lamps both operate on ballasts designed for F40T12 lamps. Use of preheat or instant start equipment will result in shorter life or reduced performance. F96T12 lamps are designed to operate on instant start ballasts. For optimum efficiency, electronic ballasts should be used wherever possible.

Ambient Temperature

Fluorescent lamps are designed and rated to operate at 60°F. Operating the lamps at higher or lower temperatures results in decreased light output, flickering and/or reduced life. High Output (HO) and Very High Output (VHO) lamps can be operated in temperatures as low as -20°F with a ballast designed for low temperatures.

Lumens

Lumens are a measurement of light output. Initial lumens are measured on a reference ballast in laboratory conditions after the lamps have been burned for 100 hours. Actual lumen output may vary depending upon ballast characteristics, fixture and ambient temperature.

Watts

Watts are measured at the lamp and do not take into consideration additional wattage that may be used by the ballast. Lamp watts plus ballast watts equal total watts consumed.

Lamp Dimensions

Published nominal lamp lengths include the lamp and two standard lamp holders.

Color Temperature

The illuminated appearance of a lamp is defined by its' color temperature expressed in degrees Kelvin. Color temperature is a simulation of the color observed when a metal object is heated. The lower temperatures begin by glowing red, then white and then blue/white. Light sources with a red-yellow glow and a color temperature of less than 3000 are considered "warm" and color temperatures of over 4000 are considered to be "cool".

Color Rendering Index (CRI)

Color Rendering Index (CRI) is a measure of how accurately colors are represented on a scale of 1 to 100 with incandescent light and sunlight at 100. Fluorescent lamps have a wide range of CRI's with the standard being "Cool White" with a CRI in the 60's. CRI's of 70-80 are considered good and 80+ is considered excellent. Since colors are truer with high CRI lamps, colors appear brighter and light levels may appear higher.

Cathode Guard

The use of a cathode guard improves lumen maintenance by reducing end blackening. All Radiant F20T12, F34T12, F40T10, F40T12, F48T12, F72T12, F96T12 and F96T12/HO lamps have cathode guards. VHO and U-Bent lamps are not available with cathode guards.

Envir-O-Light Lamps (ENV)

Lamps designed with reduced mercury content to pass the government's Toxic Characteristic Leaching Process (TCLP) test.